

## AverEPack330 Pro

Digital Slide Presenter

Preparing for a presentation is an easy and straightforward task with the **AVEREPACK330 Pro**. It is a truly **Plug-n-Play device** and displays your slide presentation on any ordinary TV, LCD/DLP projector or VGA monitor without connecting it to a PC relieving you of worries on what device to show your presentation. You can create your slides with any presentation or image-editing program. No application software is needed. It's like having a 7-in-1 card reader/writer that allows you to transfer and store all your JPEG slide \*\* to the memory card and you're ready to go.



**AVEREPACK330 Pro** includes 7-language support, delete function, transition mode variation, 16-picture preview, exclusive presentation and zoom features, and manually selects the next or previous file or randomly selects it from 16-picture preview, even enlarges and pans the picture up to 400% of its size. With an infrared remote control, it allows you to access all features with a simple touch of a button.

\*\* MS PowerPoint Slide needed to be converted into JPEG format (Baseline).

### Features:

- Display Digital format files on TV or LCD projector without connecting to PC
- Support VGA output to resolution 1024 x 768
- Plug-n-Play, No Software Driver Required
- Fully Functional Infrared Remote Control
- 3 Presentation Highlighting Functions :
  - AVerMedia Spot\*
  - AVerMedia Spotlight\*
  - AVerMedia Pointer\*
- 3 Types of Zoom :
  - Traditional Zoom & Pan
  - New AVerMedia Pointer-Zoom
  - New AVerMedia Spot-Zoom
- 90° Clockwise Image Rotation
- View True Image or Full screen
- Photo play for Auto Slide Show
- 16-pictures Preview
- Digital Zoom and Pan up to 400%
- On Screen Display Function
- Accept CF/SM/MS/SD/MMC/IBM MicroDrive
- NTSC and PAL Switchable
- Support Composite and S-Video output
- Support 4 display transition modes
- 7 Language support

### Specifications:

Input:	CF/SM/MS/MS Pro/SD/MMC/IBM MicroDrive
Output:	USB 2.0 interface TV (NTSC/PAL) or LCD projector Via Composite, S-Video, VGA Output and USB2.0 interface
Image file format:	JPEG (baseline JPEG) PowerPoint (transfer to JPEG)
Power Supply:	DC 7.5V, 600mA power adapter
Dimension	
Base Unit:	153mm 110mm 36mm
Remote Unit:	124mm 56mm 6.8mm
Operating temp:	0~40°C
Humidity:	20%~85%R.H. (at 35°C/95°F with no condensation)
Warranty:	1 year parts and labor
Safety Approval:	CE, UL
Compliance:	FCC & CE, C-tick

### Package Includes:

- AverEPack330 Pro Unit
- Remote Control with Batteries Power Adapter & Cord
- Composite Cable
- S-Video Cable
- USB Cable
- Power Adapter
- Driver CD
- Manual

\*Features subject to change without notice

**USA:** (Tel) 1-408-263-3828 (Fax) 1-408-263-8132

**U.K.:** (Tel) 44-1908-218-800 (Fax) 44-1908-218-818

**Germany:** (Tel) 49-6142-79309-0 (Fax) 49-6142-79309-37

**Spain:** (Tel) 34-91-804- 6035 (Fax) 34-91-803-7629

**China:** (Tel) 86-512-577-80908 (Fax) 86-512-577-80945

**Taiwan & International:** (Tel) 886-2-2226-3630 (Fax) 886-2-2221-4538

**Home Page:** [www.avermedia.com](http://www.avermedia.com)